Army Public School Beas

PO: Dhilwan Distt: Kapurthala Puniab: 144804

1513/APS/Interactive Panel

28 Aug 2024

CALL FOR QUOTATIONS: PURCHASE AND INSTALLATION OF INTERACTIVE PANEL FOR 11TH AND 12TH CLASSES BY APS BEAS

Dear Sir/Madam.

- 1. The quotations are hereby invited from vendors/dealers/contractors with varied experience in the field of said work. The quotations are required as appx att.
- 2. The sealed Bids are required to be addressed to Principal APS Beas and to be deposited before 1000 hrs on 10 Sep 2024. The sealed quotations box is available at the main gate of HQ 55 (I) Mech Bde.
- 3. No cutting on any figures will be accepted. The vendors/firms are at liberty to be present during bid opening for fair & transparent bidding.
- 4. <u>Validity of quotations</u>. The quotations will be valid for at the least 3 months from date of opening.
- 5. <u>Date & Time for completion of work</u>. The work is required to be completed within 20 working days from the issue of supply order.
- 6. <u>Force majeure</u>. The school will not be responsible for any untoward / unforeseen requirements as generated at the vendors end.
- 7. Payments. The payments will be made by the school within 07 days after inspection of work at APS Beas within stipulated time.
- 8. <u>Demurrage</u>. Late work scheduled will be charged demurrage @ 5% for delayed time scheduled of the project cost.
- 9. <u>Manufacturing guarantee / warranty</u>. The contractor firm will be responsible for any defect or maintenance or low quality work / performance / material. If found any during inspection by the authority of school. Adequate charges will be levied from the bills paid by the school. The school deserves the right to cancel / modify the supply order / schedule of work at any stage as per requirement of the school.
- 10. Please also mention "Purchase and Installation of Interactive Panel" on the top outside of envelope.

Yours faithfully,

(Pankaj Verma)

Bursa

CALL FOR QUOTATIONS: PURCHASE AND INSTALLATION OF INTERACTIVE PANEL FOR 11TH AND 12TH CLASSES BY APS BEAS

er	Description		Qty	Amount
)	Consult Internative De	anel 75" android 13.0 4/64 with wall mount kit	02	
	Smart Interactive Pa	anel 75 android 13.0 4/04 with wait mount kit		
	Display			
	Screen Size	: 75 inch		
		DIED		
	Pixel Pitch	: 0.143 (H) mm×0.430 (V) mm		
	Resolution	: 3840 × 2160 @60 Hz		
	Brightness	: DLED : 0.143 (H) mm×0.430 (V) mm : 3840 × 2160 @60 Hz : 400 cd/m² (Typ.) : 10 bit : 1.07G		
	Color Depth	: 10 bit		
	Display Color	· 1 07G		
	Response Time	· 8ms		
	Panel Type			
	Contrast Ratio			
		45 000.4 (Dumamia)		
	Calar Camut	: 72% NTSC (CIE1931) (Typ.) : 60 Hz		
	Color Gamut	. 72% N130 (CIE 1931) (Typ.)		
	Viewing Angle	. 470°(L)(470°(A)		
	Viewing Angle	: 1/8 (H)/1/8 (V)		
	Aspect Ratio	: 16:9		
	Surface Haze	: 25% Haze		
	Display Area	: 1649.66mm × 927.94mm : 7 × 16H : 9H		
	Working Duration	: 7 × 16H		
	Surface Hardness	: 9H		
	Surface Glass	: 3.2 mm Anti-Glare Glass		
	Transmittance	: 88% ± 3		
	Lifespan	: 50,000 hours		
	Touch			
	Туре	: Infrared Touch Screen : 40-point multi-touch		
	Touch Point	: 40-point multi-touch		
	Touch Response Tim	ne : < 5 ms		
	Minimum Touch Obje	ect : ≥ 2 mm		
	Touch Precision	: ± 1 mm (≥ 90% touching area)		
	Touch Resolution	: 32768 × 32768		
	Built-in System			
	Operation System	: Android 13.0		
	Memory	: 8 GB		
	Built-in Storage CPU	: 64 GB		
	CPU	: Cortex-A55 × 4 (1.92GHz)		
	HDCP Version	: Support 1.4/2.2/2.3		
	GPU	: Mali-G52 MP2 (2EE)		
	Internal Function			
	Loudspeaker	: Built-in 2 × 20 W		
	Speaker Frequency	: 200-20Khz		
	Bluetooth	: Built-in BLE (Bluetooth Low Energy) module		
		supports Bluetooth 5.2		
	NFC	: Support card reader		
		: Yes		

	2	Qty	Amount
	inton		
D	escription		
	iterface ideo & Audio Input : HDMI In (HDMI 2.0)×2, Audio In×1 ideo & Audio Output : Audio Out × 1 RS232×1, LAN (100 Mbps)		
In	ideo & Audio Input : HDMI In (HDMI 2.0)**2, sideo & Audio Output : Audio Out × 1 ideo & Audio Output : Audio Out × 1 TOUCH-USB 2.0×1, RS232×1, LAN (100 Mbps) TOUCH-USB 2.0×1, RS232×1, LAN (100 Mbps) TOUCH-USB 2.0×1, RS232×1, LAN (100 Mbps)		
VI	ideo & Audio Output : Audio Out × 1 ideo & Audio Output : Audio Out × 1 ideo & Audio Output : TOUCH-USB 2.0×1, RS232×1, LAN (100 Mbps) ideo & Audio Output : TOUCH-USB 2.0×1, RS232×1, LAN (100 Mbps)		
C	ontrol Interface TOUCH-USB 2.0×1, R324G/5G Station, 2.4G/5G × 2, WIFI AP & Station, 2.4G/5G		
N	x 2, WIFI AP & Station a/b/g/n/ac 2×2 WIFI AP : IEEE 802.11 a/b/g/n/ac 2×2 WIFI AP : IEEE 802.11 a/b/g/n/ac 2×2 WIFI AP : IEEE 802.11 a/b/g/n/ac 1×1 WEP, WPA, WPA2, PSK and 802.1X EAP WEP, WPA, WPA2, PSK and 802.1X EAP WEP, WPA, WPA2, PSK and 802.11 a/b/g/n/ac 1×1 WEP, WPA2, PSK and 802.11 a/b/g/n/ac 1×1 WEP, WPA2, WPA2, PSK and 802.11 a/b/g/n/ac 1×1 WEP, WPA2, WPA2, PSK and 802.11 a/b/g/n/ac 1×1 WEP, WPA3,		
	(2.4 GHz and 5 GHz) WEP, WPA, WPA2, PSK and 802.1X EAP WEP, WPA3, WPA4, WPA4, PSK and 802.1X EAP WEP, WPA4, WPA4, WPA4, PSK and 802.1X EAP WEP, WPA4, WPA4, WPA4, PSK and 802.1X EAP WEP, WPA5, WPA4, WPA4, PSK and 802.1X EAP WEP, WPA5, WPA5, WPA5, PSK and 802.1X EAP WEP, WPA5, WPA5, WPA5, PSK and 802.1X EAP WEP, WPA5, WP		
	WEP, WPA, WPA2, 1 802.11 a/b/g/n/ac 1 WIFI Station: IEEE 802.11 a/b/g/n/ac 1 WIFI Station: IEEE 802.11 a/b/g/n/ac 1 WIFI Station WIFI WPA2, PSK and 802.1X		
	MIMO (2.4 GHZ and WPA2, PSK and 802.17		
	WIFI Station: IEEE 802.1 authentication MIMO (2.4 GHz and 5 GHz) authentication MIMO (2.4 GHz) a		
	EAP 30 x 3 USB 2.0 x 2, Type-0		
	protocols WEP, WFA, The protoc		
1	Data Transmission (Type-C support		
	50/60 Hz		
	Power Supply : 100 to 240 VAC, 50/00 1.2 Power Supply : 5 0.5 W		
	Power Supply Standby Consumption: ≤ 0.5 W Standby Consumption: 217 W		
	May Consumption 475 M		
	A PROGRAMMENT OF FIRM		
	General 1713.23 mm × 1025.53 mm × 223 mm		
	Average Consumption: 175 W Average Consumption: 175 W General Product Dimensions: 1713.23 mm × 1025.53 mm × 82.5 mm Package Dimensions: (W×H×D): 1907mm × 1160mm × 223 mm Package Dimensions: 800mm×400mm (4×M8-25 mm)		
	Package Difference 800mm×400mm (4		
	VESA 49.15 kg		
	Net Weight Gross Weight Gross Weight Access AV Wall mount bracket, hook, user manual, stylus ×		
	Gross Weight Accessary Accessary		
	Accessary 2, packing list, 1.5 m plants and ard), remote controller standard), remote controller		
	Standard)		
	Working Environment Working Temperature: 0 °C to 40 °C (32 °F to 104°F) Working Temperature: 10%~90% RH		
	Working Temperature : 0 0 to 10 Working Humidity : 10%~90% RH	-	
	Working Humary		
2.	Freight	_	
3.	Installation	-	
1.	GST Any other Charges if applicable		
5.			
6.	Total	41	- alvos of all

- 1. Tenderers shall carefully examine the bid documents and fully inform themselves of all the conditions which may in any way affect the work of the cost thereof.
- Should a tenderer find discrepancies or omission from the specification or other documents and any doubt as to their money, he should at once notify the purchaser and clarification in writing.

any doubt as to their money, he should at once not any doubt as to their money, he should at once not any doubt as to exiting structure/ construction w		he rectifying by vendors by their own expenses.
3.	Any loss to exiting structure/ construction will	(Name of vendor) stating that I / we have

3.	Any loss to exiting structure/ construction will be resemble.	(Na	me of v	endor)	statin	g that	1 / w visit	e ha	on
4. unders	I / we	the	school	during	, the	prior			

Signatures :	
Name & Place/Address of firm with stam	p
Mobile No :	-

ile No.

ol. No.